

Business Name:		Contact Name:	
Address:		Phone:	
ARD # :		Number of Technicians:	
EPA ID # :		Number of Cars/Month:	
		Number of Paint Booths:	
DTSC Green Station Pollution Prevention (P2) Checklist			
for Auto Body and Paint Shops			
Circle	Note: Items with * next to points are required items		
10	Conduct a P2 Assessment using the P2 Opportunities Checklist for Vehicle Service & Repair.		
10	Designate sanding preparation area away from painting.		
5	Use high efficiency sand paper.		
15*	Use vacuum sanding system (portable or central) OR Dust control method and collect after each sanding task. Must show proper waste disposal and waste determination.		
10	Minimize water for wet sanding process- for example spray nozzle or reuse water.		
10	Use computerized paint mixing system.		
10*	Apply coatings in paint booth.		
15*	Use waterborne and low VOC coatings, thinners, and paint gun cleaners. (Meets CARB Suggested Control Measure).		
10*	Use non-toxic or reduced toxicity paint gun cleaning products that meet CARB or local VOC limits (Does not contain TBAC, PCBTF, toluene, for example).		
10	Painters are trained in efficient spray application techniques and routinely use paint minimization methods when mixing and applying coatings.		
10*	Maintain paint booth - intake and exhaust filters are replaced regularly, fans and walls cleaned or covered.		
5	Conduct preventative maintenance on air compressor for spray equipment.		
5	Use a fully enclosed waste transfer system for waste liquids (funnels with lids and spill prevention methods to transfer paint, thinners, etc).		
5*	Use & maintain drip pans in outside areas to control fluid leakage.		
10*	Store hazardous materials and wastes in covered area with secondary containment away from storm & sewer drains.		
10*	Business Response Plans are submitted and updated annually to local agencies.		
5	Emergency spill kits are available (mats, plugs, etc.).		
2	Stencil all storm drains "No Dumping ... Flows to waterway".		
2	Post warning signs (min. 5"x 8") above sink areas "Do Not Discharge Hazardous Wastes or Chemicals Down Any Work Sink or Drain".		
5	Use an industrial launderer for shop towels (shop rag contract).		
15	Install closed loop vehicle washing system.		
5	Seal shop floor with an impermeable coating; or polish and seal.		
10*	No open drains, or seal existing drains in service areas.		
5	Store spent batteries in secondary containment, covered if outdoors.		
5	Replace lead tire/wheel weights with steel weights if tires are sold. Recycle lead tire/wheel weights.		
5	Use recycled content products.		
10	Additional pollution prevention alternatives implemented at facility (list) :		
	Total Points (125 or more Points needed for Green Station Recognition)		
	Signature:		Date:
			5/23/2011